

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830. Issue date: 22/08/2023 Revision date: 10/01/2024 Supersedes: 22/08/2023 Version: 1.1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

 Product form
 : Mixture

 Trade name
 : (Aerosol) Jelsol

 Product code
 : 003498000029

 Vaporizer
 : Aerosol

Synonyms : AJEL001D / AJEL062D / AJEL009D

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Solvent cleaner, cold cleaner

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

**AUTOSMART INTERNATIONAL** 

9 Attwood Road

WS7 3GJ Burntwood - Staffordshire ENGLAND

T +44 (0) 1543 481616 (09:00 - 17:00)

SHREQ@autosmart.co.uk - www.autosmartinternational.com

#### 1.4. Emergency telephone number

Emergency number

: NCEC - For Chemical Emergency Support ONLY (spill, leak, fire, exposure or accident), Call NCEC at +44 1865 407333 (24Hrs UK)

when calling please quote "AUTOSMART 29003-NCEC"

If you urgently need medical help or advice but it's not a life-threatening situation, call 111 free from any phone to speak to an NHS adviser. The 24-hour NHS 111 service can give you healthcare advice or direct you to the local service that can help you best.

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for UK law

Aerosol, Category 1 H222;H229
Acute toxicity (dermal), Category 4 H312
Acute toxicity (inhalation:vapour) Category 4 H332
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Respiratory H335
tract irritation

Specific target organ toxicity – Repeated exposure, Category 2 H373

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause damage to organs through prolonged or repeated exposure. Harmful in contact with skin. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP], as amended for UK law

Hazard pictograms (CLP)







GHS02

GHS07

GHS08

Signal word (CLP)

Contains

: Danger

Hazard statements (CLP)

: Xylene (mixture of isomers); Ethylbenzene; methanol : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated. H312+H332 - Harmful in contact with skin or if inhaled.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation. H335 - May cause respiratory irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P260 - Do not breathe vapours, spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, eye protection. P302+P352 - IF ON SKIN: Wash with plenty of water.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

# 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

# 3.2. Mixtures

Name	Product identifier	%	Labelling according to Regulation
			(EC) No. 1272/2008 [CLP], as amended for UK law
Xylene (mixture of isomers) substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	≥ 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) substance with national workplace exposure limit(s) (BE, CZ, GB, GR, HR) (Note K)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	20 – 24.9	Flam. Gas 1A, H220 Press. Gas
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics substance with national workplace exposure limit(s) (PL, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 919-857-5	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066
Ethylbenzene substance with national workplace exposure limit(s) (AT, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	5 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
methanol substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	0.5 – 1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) STOT SE 1, H370
Quartz (SiO2) substance with national workplace exposure limit(s) (AT, BE, DK, EE, ES, FI, FR, HR, IE, LT, NL, PL, PT, SE, SK, NO, MK, CH); substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	0.1 – 0.2	Not classified
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine substance with national workplace exposure limit(s) (DE, CH)	CAS-No.: 110-25-8 EC-No.: 203-749-3	< 0.1	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 3, H412

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	(3 ≤ C < 10) STOT SE 2, H371 (10 ≤ C ≤ 100) STOT SE 1, H370	

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the

supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than

0.1% w/w 1.3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least

the precautionary statements (P102-)P210-P403 shall apply.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a

doctor if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing.

### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Mechanically recover the product.

Other information

: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only outdoors or in a well-ventilated area.

Hygiene measures

Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

ylene (mixture of isomers) (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name Xylene, mixed isomers, pure		
IOEL TWA	221 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm] 100 ppm		
Remark	Skin	

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Xylene (mixture of isomers) (1330-20-7)				
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
United Kingdom - Occupational Exposure Limits				
Local name	Xylene			
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers			
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers			
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers			
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers			
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
United Kingdom - Biological limit values				
Local name	Xylene, o-, m-, p- or mixed isomers			
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
Ethylbenzene (100-41-4)				
EU - Indicative Occupational Exposure Limit (IOEL)				
Local name	Ethylbenzene			
IOEL TWA	442 mg/m³			
IOEL TWA [ppm]	100 ppm			
IOEL STEL	884 mg/m³			
IOEL STEL [ppm]	200 ppm			
Remark	Skin			
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
United Kingdom - Occupational Exposure Limits				
Local name	Ethylbenzene			
WEL TWA (OEL TWA) [1]	441 mg/m³			
WEL TWA (OEL TWA) [2]	100 ppm			
WEL STEL (OEL STEL)	552 mg/m³			
WEL STEL (OEL STEL) [ppm]	125 ppm			
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes	, cyclics, < 2% aromatics (64742-48-9)			
EU - Indicative Occupational Exposure Limit (IOEL)	EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	White spirit Type 3			
IOEL TWA	116 mg/m³			
IOEL TWA [ppm]	20 ppm			
IOEL STEL	290 mg/m³			
IOEL STEL [ppm]	50 ppm			
-	·			

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)						
Remark	Skin. (Year of adoption 2007)					
Regulatory reference	SCOEL Recommendations					
Quartz (SiO2) (14808-60-7)	Quartz (SiO2) (14808-60-7)					
EU - Indicative Occupational Exposure Limit (IOEL)						
Local name	Silica crystaline (Quartz)					
IOEL TWA	0.05 mg/m³ (respirable dust)					
Remark	(Year of adoption 2003)					
Regulatory reference	SCOEL Recommendations					
methanol (67-56-1)						
EU - Indicative Occupational Exposure Limit (IOEL)						
Local name	Methanol					
IOEL TWA	260 mg/m³					
IOEL TWA [ppm]	200 ppm					
Remark	Skin					
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC					
United Kingdom - Occupational Exposure Limits						
Local name	Methanol					
WEL TWA (OEL TWA) [1]	266 mg/m³					
WEL TWA (OEL TWA) [2]	200 ppm					
WEL STEL (OEL STEL)	333 mg/m³					
WEL STEL (OEL STEL) [ppm]	250 ppm					
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)					
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE					
Petroleum gases, liquefied (Contains < 0.1% 1	,3-butadiene) (68476-85-7)					
United Kingdom - Occupational Exposure Limits						
Local name	Liquefied petroleum gas					
WEL TWA (OEL TWA) [1]	1750 mg/m³					
WEL TWA (OEL TWA) [2]	1000 ppm					
WEL STEL (OEL STEL)	2180 mg/m³					
WEL STEL (OEL STEL) [ppm]	1250 ppm					
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))					
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE					

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

### Personal protective equipment symbol(s):







### 8.2.2.1. Eye and face protection

### Eye protection - Report preview:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses			EN 166

### 8.2.2.2. Skin protection

### Skin and body protection - Report preview:

Wear suitable protective clothing

### Hand protection - Report preview:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves					EN ISO 374

### 8.2.2.3. Respiratory protection

## Respiratory protection - Report preview:

[In case of inadequate ventilation] wear respiratory protection.

### 8.2.2.4. Thermal hazards

No additional information available

## 8.2.3. Environmental exposure controls

# Environmental exposure controls:

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Beige.
Appearance : Aerosol.
Odour : Not available
Odour threshold : Not available
Melting point : Not applicable

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

**Explosive limits** Not available Flash point < -40 °C Auto-ignition temperature Not available Decomposition temperature Not available : Not available Viscosity, kinematic  $: > 20.5 \text{ mm}^2/\text{s}$ Solubility : Not available Partition coefficient n-octanol/water (Log Kow) Not available Vapour pressure Not available Vapour pressure at 50°C Not available Density Not available Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

#### 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 96.384 %

9.2.2. Other safety characteristics

VOC content : 742 g/l

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK Law.

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Harmful if inhaled.

(Aerosol) Jelsol		
	ATE CLP (dermal)	1977.161 mg/kg bodyweight
	ATE CLP (vapours)	16.92 mg/l/4h

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

in corrosion/irritation : Causes skin rious eye damage/irritation : Causes serious eye damage/irritation : Not classified : May cause responsive : May cause responsive : May cause responsive : May cause : May cau	eus eye irritation.  d d d d espiratory irritation.			
rious eye damage/irritation : Causes serior spiratory or skin sensitisation : Not classified rm cell mutagenicity : Not classified rcinogenicity : May cause rcinogenicity : May cause rcinogenicity : May cause rcinogenet rcinogenicity : May cause rcinogenet rcinogenicity : May cause rcinogenet rcinog	ous eye irritation.  d d d d d espiratory irritation.  2% aromatics (64742-48-9) drowsiness or dizziness.  hage to organs.			
ylene (mixture of isomers) (1330-20-7)  TOT-single exposure May cause of ydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < TOT-single exposure May cause of ethanol (67-56-1)  TOT-single exposure Causes dan OT-repeated exposure : May cause of ylene (mixture of isomers) (1330-20-7)  DAEL (oral, rat, 90 days) 150 mg/kg to (Repeated Day Oral To	respiratory irritation.  2% aromatics (64742-48-9)  drowsiness or dizziness.  nage to organs.			
ydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < TOT-single exposure  May cause of the control of the con	2% aromatics (64742-48-9) drowsiness or dizziness.  hage to organs.			
TOT-single exposure  May cause of the thanol (67-56-1)  TOT-single exposure  OT-repeated exposure  Causes dan of the thanol (67-56-1)  May cause do not cause described by the thanol (67-56-1)  DAEL (oral, rat, 90 days)  TOT-single exposure  Substituting the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the than cause of the thanol (67-56-1)  TOT-single exposure  Substituting than cause of the than c	drowsiness or dizziness.			
rot-single exposure  OT-repeated exposure  Other (mixture of isomers) (1330-20-7)  OAEL (oral, rat, 90 days)  Causes dan  Causes dan  150 mg/kg kg (Repeated IDay Oral To	nage to organs.			
Causes dan OT-repeated exposure : May cause d ylene (mixture of isomers) (1330-20-7)  DAEL (oral, rat, 90 days)  150 mg/kg k (Repeated I Day Oral To				
OT-repeated exposure : May cause d  ylene (mixture of isomers) (1330-20-7)  DAEL (oral, rat, 90 days)  150 mg/kg b (Repeated Day Oral To				
ylene (mixture of isomers) (1330-20-7)  DAEL (oral, rat, 90 days)  150 mg/kg k (Repeated Day Oral To	amage to organs through prolonged or repeated exposure.			
DAEL (oral, rat, 90 days)  150 mg/kg b (Repeated I Day Oral To				
(Repeated I Day Oral To				
FOT-repeated exposure May cause of	oodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-xicity)			
	damage to organs through prolonged or repeated exposure.			
Ethylbenzene (100-41-4)				
TOT-repeated exposure May cause of	damage to organs through prolonged or repeated exposure.			
etroleum gases, liquefied (Contains < 0.1% 1,3-butadie	ne) (68476-85-7)			
	Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose dy with the Reproduction / Developmental Toxicity Screening Test), Guideline:			
piration hazard : Not classified	I			
Aerosol) Jelsol				
aporizer Aerosol				
scosity, kinematic > 20.5 mm²/	s			
thylbenzene (100-41-4)				
scosity, kinematic  0.6 mm²/s T 'other:'				

### 11.2. Information on other hazards

No additional information available

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Hazardous to the aquatic environment, short-term

(acute)

: Not classified

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Hazardous to the aquatic environment, long-term

: Not classified

(chronic)

Not rapidly degradable

Xylene (mixture of isomers) (1330-20-7)		
EC50 - Crustacea [1] > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia		
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20  $^{\circ}\text{C}$  and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
  - HP5 "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
  - HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
  - HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

ADR	IMDG	IATA	ADN	RID				
14.1. UN number or ID number								
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950				
14.2. UN proper shippin	14.2. UN proper shipping name							
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS				
Transport document descr	iption							
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1				
14.3. Transport hazard	class(es)							
2.1	2.1	2.1	2.1	2.1				
2	*	2	2	2				
14.4. Packing group								
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable				
14.5. Environmental hazards								
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No				
No supplementary information	on available		1	1				

# 14.6. Special precautions for user

# Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200
Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

# Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959 Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

# Air transport

PCA Excepted quantities (IATA) : E0

## Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID): 1LExcepted quantities (RID): E0Packing instructions (RID): P207, LP200Special packing provisions (RID): PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

# 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

# **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content : 742 g/l

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

No additional information available

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Abbreviations and acronyms:		
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH	Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4		
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4		
Aerosol 1	Aerosol, Category 1		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H301	Toxic if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H311	Toxic in contact with skin.		
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		

# Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Full text of H- and EUH-statements:		
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H370	Causes damage to organs.	
H371	May cause damage to organs.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H412	Harmful to aquatic life with long lasting effects.	
Press. Gas	Gases under pressure	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 1	Specific target organ toxicity – single exposure, Category 1	
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	

Safety Data Sheet (SDS), UK

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.